US 20220104457A1

(19) **United States**

(12) **Patent Application Publication**

Narita et al.

(10) **Pub. No.: US 2022/0104457 A1**

(43) **Pub. Date: Apr. 7, 2022**

(54) **GUIDANCE VEHICLE**

(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Toyota-shi Aichi-ken (JP)

(72) Inventors: **Saki Narita**, Toyota-shi Aichi-ken (JP); **Tetsuya Kanata**, Susono-shi Shizuoka-ken (JP); **Yozo Iwami**, Susono-shi Shizuoka-ken (JP); **Daisaku Honda**, Nagoya-shi Aichi-ken (JP); **Yuhei Katsumata**, Fuji-shi Shizuoka-ken (JP); **Hideki Fukudome**, Toyota-shi Aichi-ken (JP); **Takuya Watabe**, Hachioji-shi Tokyo-to (JP); **Naoko Ichikawa**, Shibuya-ku Tokyo-to (JP); **Yuta Maniwa**, Susono-shi Shizuoka-ken (JP); **Yuki Nishikawa**, Susono-shi Shizuoka-ken (JP); **Daisuke Ishii**, Sunto-gun.Shizuoka-Ken (JP); **Daisuke Sato**, Susono-shi (JP)

(21) Appl. No.: **17/476,792**

(22) Filed: **Sep. 16, 2021**

(30) **Foreign Application Priority Data**

Oct. 2, 2020 (JP) 2020-168057

Publication Classification

(51) **Int. Cl.**

A01K 15/02	(2006.01)
A01K 29/00	(2006.01)
A01K 27/00	(2006.01)
B25J 9/00	(2006.01)
B25J 9/16	(2006.01)
B25J 11/00	(2006.01)
G05D 1/02	(2006.01)

(52) **U.S. Cl.**

CPC ***A01K 15/02*** (2013.01); ***A01K 29/005*** (2013.01); ***A01K 27/004*** (2013.01); ***B25J 9/0003*** (2013.01); ***G05D 1/0246*** (2013.01); ***B25J 9/163*** (2013.01); ***B25J 11/008*** (2013.01); ***G05D 1/0223*** (2013.01); ***B25J 9/0009*** (2013.01)

(57) **ABSTRACT**

A guidance vehicle guides a dog for a walk, and includes a leash attachment, a distance sensor, and an electronic control unit. The leash attachment is configured to attach a leash that connects the dog. The distance sensor is configured to detect a dog-to-vehicle distance being a distance between the dog and the guidance vehicle. The electronic control unit is configured to execute a travel control of the guidance vehicle. The electronic control unit includes, as one of modes of the travel control, a walk guidance mode that causes the guidance vehicle to automatically travel along a walk route while guiding the dog to walk. The walk guidance mode executed by the electronic control unit includes a basic walk mode that controls the dog-to-vehicle distance so as to maintain a constant distance when the dog is moving along the walk route.